

In the Claims

Please replace all prior versions, and listings, of claims in the application with the following list of claims:

1. (Currently Amended) A pipette module comprising:
a channel block having at least one passage extending therethrough;
a rod sized, shaped and aligned to pass into the channel block passage;
a cylinder having an axially extending passage therethrough sized, shaped and aligned to pass into the channel block passage from the end opposite the end into which the rod passes;
a chamber defined by the channel block, rod, and cylinder, having a volume which is variable during operation of the pipette module, with a first part of the chamber variable by relative movement of the channel block relative to the fixed relative positions of the rod and cylinder, and with a second part of the chamber variable by relative movement of the cylinder relative to the fixed relative positions of the rod and channel block.
2. (Original) The pipette module of claim 1, wherein a third part of the chamber is variable by relative movement of the rod relative to the fixed relative positions of the channel block and cylinder.
3. (Original) The pipette module of claim 1, wherein the diameter of the rod is greater than the diameter of the cylinder, providing an annular space between the inner surface of the channel block and the outer surface of the cylinder, defining said first part of the chamber.
4. (Previously Presented) The pipette module of claim 2, wherein the diameter of the rod is less than the inner diameter of the channel block, providing an annular space between the inside surface of the channel block and the outside surface of the rod, defining said third part of the chamber.

5. (Previously Presented) The pipette module of claim 1, further comprising:
a tip having a passageway therethrough, extending downwardly from the bottom of the cylinder; and
an extension mandrel with a passageway extending therethrough, the mandrel attached at an end of the cylinder such that the passageway extending through the mandrel is aligned with the passage extending through the cylinder, wherein the mandrel reduces the internal volume within the tip.
6. (Previously Presented) The pipette module of claim 5, wherein the extension mandrel is removably secured to the cylinder.
- 7- 44. (Canceled)
45. (Previously Presented) The pipette module of claim 1, wherein no portion of the rod extends into the passage extending through the cylinder.